



The left picture shows: Steady Stand 500, a low model, placed under the press table. 3-wheel adapter ensures stability on uneven surfaces. Conveyor, feeding tray and control box are mounted directly on the stand.

## Steady Stand

Floor stand for Black Line ECS-141 or ECS-121 conveyor is designed to flexible move the complete conveyor unit between various manufacturing machines. The stand is either fitted with machine feet or wheels with brakes.

|   |   |
|---|---|
| Material (laser cut)                        | 5 mm high strength steel                |
| Surface                                     | painted grey                            |
| Max load                                    | 100 kg                                  |
| Diameter of wheel                           | 125 mm                                  |
| Ball bearing wheel with foot operated brake | 3/4 pcs polyurethane tyres              |
| Integrated fork lift attachment             | 4 pcs polyurethane machine feet         |
| Dimensions with wheel (LxWxH)               | 700x500x(customized height max.1300 mm) |
| Dimensions with feet (LxWxH)                | 700x680x(customized height max.1300 mm) |
| Weight                                      | 110 kg                                  |

### Adress:

Conveyor 22 AB  
Gränumsvägen 390  
293 93 Olofström, Sweden

### Phone:

+46 (0)454-432 21

### E-mail:

kontakt@conveyor22.se

### Internet:

www.conveyor22.se

### VAT no:

556881-0393  
SE556881039301