Conveyor 22®
Clean Electrical Engineering

Made in Sweden

Clean Line 181

Patented electric linear conveyor with intelligent and maintenance free technology. Manufactured in stainless steel and anodized aluminum. IP66, dust and splash proof. Suitable for pharmaceutical industry, food process or harsh environments. A decrease of feeding speed results in an increase of max distributed and attached loads. The conveyor is delivered as a complete unit including control box.

Max distributed load (in highest feeding speed)	10 kg
Max attached load (in highest feeding speed)	4 kg
Stroke	20 mm
Feeding speed (mechanical adjustable)	4-8 m/min
Built-in warning system (motion sensor)	M12 connector
Start/Stop can be controlled from PLC	M12 connector
Motor and overload protection	built-in
Noise level	60 dB(A)
Energy consumption	0.05 kW
Electricity	110-230 VAC, 50-60 Hz or 24 VDC
Protection class	IP66
Dimensions (LxWxH)	271x118x38 mm
Weight	2.65 kg

Adress:
Conveyor 22 AB
Gränumsvägen 390
293 93 Olofström, Sweden

Phone:
+46 (0)454-432 21

E-mail:
kontakt@conveyor22.se

Internet:
www.conveyor22.se

VAT no:
556881-0393
SE556881039301

© Conveyor 22 AB 2019-02