Conveyor 22®
Clean Electrical Engineering

Made in Sweden

Black Line 121

Patented electric linear conveyor with intelligent and maintenance free technology. Manufactured in high strength steel and anodized aluminum. IP62, suitable for most manufacturing industries. A decrease of feeding speed results in an increase of max distributed and attached loads. The conveyor is delivered as a complete unit including control box.

Max distributed load (in highest feeding speed)	40 kg
Max attached load (in highest feeding speed)	16 kg
Stroke	20 mm
Feeding speed (mechanical adjustable)	4-8 m/min
Built-in warning system (motion sensor)	M12 connector
Start/Stop can be controlled from PLC	M12 connector
Motor and overload protection	built-in
Noise level	60 dB(A)
Energy consumption	0.15 kW
Electricity	110-230 VAC, 50-60 Hz or 24 VDC
Protection class	IP62
Dimensions (LxWxH)	318x138x68 mm
Weight	6.3 kg

RoHS Compliant

Adress:
Conveyor 22 AB
Gränumsvägen 390
293 93 Olofström, Sweden

Phone:
+46 (0)454-432 21

E-mail:
kontakt@conveyor22.se

Internet:
www.conveyor22.se

VAT no:
556881-0393
SE556881039301

© Conveyor 22 AB 2019-02